FORM 126 5 58	Approved For Release 20	04/05/13:56/A:RDR89800980R0	0000000075-4	. 1944 - 1944 DISTO CONTRACTOR AND
	43	STATE OF THE SECURIOR CONTRACTOR OF THE SERVICE CONTRACTOR CONTRACTOR STATE CO. S. C.		9
DATE	9016Z 10 DEC 64	SECRET	3	110
	***	TO COMMENT OF THE PROPERTY OF	1 4	12
			= 5	13
70 :	DIRECTOR	ROUTING INT	6	14
constant		1	<u> </u>	15
FPROES :		2		(STACE VALLE) (TENNES ESTAC TENNES ESTACE) (TENNES ESTACE) (TENNES ESTACE) (TENNES ESTACE) (TENNES ESTACE) (TE POR TENNES ESTACE (TENNES ESTACE) (TENNES ESTACE) (TENNES ESTACE) (TENNES ESTACE) (TENNES ESTACE) (TENNES ESTACE)
ACTION:		3   4		PRIORITY
mro :		15	E STANCES PROPERTY STANCES	
70	R: 0041Z 10 DEC 64	7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	10 G	IN 6125331A
TO PI	NIORITY INF	2	5X1A CITE	
	CART FLIEST OF	<b>"</b>	47.00	R
		The second section of the s	•	005.63
M	NITE ACTION			m.0
	1. ARTICLE 131 MADE FLIGHT 27. ON 9 DECEMBER 1964, PILOT			
	TAKE OFF AT 1236 HOURS FROM 1 HOUR AND 14 MINUTES.			
	$\mathcal{N} = \mathcal{N} \mathcal{N} $			
M	MISSION: TEST OF SYSTEMS "A" AND "D". GROSS WEIGHT 111,300 LBS.			
	C.G. 20.8 PERCENT. TAKE OFF DISTANCE 5800 FEET TAKE OFF SPEED 226			
		DE 4411, TEMPERATURE 52		
3.	336 DEGREES AND 12 KNOTS. MAXIMUM SPEED 1.38 MACH, MAX ALT 47,000.			
	2. PILOT TRIMMED UP THE LEFT ENGINE 100 DEGREES PRIOR TO TAKE			
	OFF AND TRIMMED THE RIGHT ENGINE DOWN SLIGHTLY. THE RIGHT AB LIT			
S	SLOW (2 SECONDS) ON THE GROUND AND IN THE AIR. CLIMBED TO 45,000			
	FEET FLEW PATTERN TO OPERATE SYSTEMS "A" AND "D". AB REQUIRED			
F	FOR FLIGHT AT 45,000 FEET. EXERCISED BOTH			
	PILOT. WHEN HEADING HOLD FEATURE OF AUTOPILOT WAS ENGAGED DURING			
	25 DEGREE BANKED TURN, RECOVERY ROLL RATE WAS EXCESSIVE (1 SECOND)			
ŗ	AND A 12 DEGREE OVERSHOOT ON HEADING OCCURRED FOLLOWED BY ANOTHER			
c	CORRECTION TO SELECTED HEADING. AFTER REACHING 8000 LBS FUEL			
	REMAINING, DESCENT AND LANDING MADE. CHUTE OPERATION NORMAL.			
	end of message	SECRET	MATERIAL CONTROL STATES OF THE SERVICE CONTROL	ANG.
	REPRODUCTION BY OTHER	THAN THE ISSUING OFFICE IS I		opy no. 2